

## SPECIFICATION

TO ALL WHOM IT MAY CONCERN:

BE IT KNOWN THAT WE, Takehiro Ikeda, a citizen of Japan residing at 18-4-1101, Nobi 4-chome, Yokosuka-shi, Kanagawa 239-0841 Japan, Ichiro Okajima, a citizen of Japan residing at 968-12-1-302, Mitsuura-cho, Kanazawa-ku, Yokohama-shi, Kanagawa 236-0032 Japan and Narumi Umeda, a citizen of Japan residing at 40-14, Tomioka-Nishi 6-chome, Kanazawa-ku, Yokohama-shi, Kanagawa 236-0052 Japan have invented certain new and useful improvements in

## RETRANSMISSION CONTROL METHOD AND THE APPARATUS

of which the following is a specification:-

# RETRANSMISSION CONTROL METHOD AND THE APPARATUS

## 1. Field of the Invention

2. Description of the Related Art

Conventionally, a method of sending acknowledgment is usually adopted as a retransmission control method in communication systems. In this method, when a receiver receives a signal which is sent from a sender, the receiver judges whether the signal is correctly received, that is, whether the signal includes an error. When the signal is correctly received, the receiver sends ACK (acknowledgement) which indicates that retransmission is unnecessary to the sender. When the signal is not correctly received, the receiver sends NACK (negative acknowledgement) for requesting retransmission to the sender. When the sender receives NACK, the sender retransmits a signal corresponding to the previously transmitted signal.

This retransmission control method is also adopted in a communication system in which mobile stations and base stations communicate each other via communication channels. For example, as far as retransmission control for a signal sent from a mobile station to a base station (which will be called an up-link signal hereinafter) is considered, an mobile station which plays a role of a sender sends a signal to a corresponding base station with which the mobile station communicates, that is, a communication partner of the mobile station. The



each of the base stations performing error judgment for the signal sent from the mobile station;

5 a corresponding base station of a communication partner of the mobile station obtaining results of error judgment of the corresponding base station and other base stations;

10 the corresponding base station sending a response which indicates that retransmission is not required to the mobile station when at least one result indicates that there is no error; and

15 the corresponding base station sending a response which indicates that retransmission is required to the mobile station when every result indicates that there is an error.

20 According to this retransmission control method, every base station which received the up-link packet from the mobile station performs error judgment, and, when at least one base station judges that there is no error, ACK signal which indicates that retransmission is not required is sent to a mobile station by the corresponding base station.

25 Therefore, retransmission process is reduced maximally so that effective retransmission control becomes possible. As a result, load of retransmission process can be reduced and communication channels can be used effectively.

30 The above object is also achieved by a retransmission control method including the steps of:

base stations receiving a signal sent from a mobile station;

each of the base stations performing error judgment for the signal sent from the mobile station;

35 the base stations exchanging results of

the error judgment with one another;

5 a corresponding base station sending a response which indicates that retransmission is not required to the mobile station when at least one result from the base stations indicates there is no error; and

10 the corresponding base station sending a response which indicates that retransmission is required to the mobile station when every result from the base stations indicates that there is an error.

15 Also according to this retransmission control method, retransmission process is reduced maximally so that effective retransmission control can be possible. As a result, load of retransmission process can be reduced and communication channels can be used effectively.

20 In the retransmission control method, a value of received signal power level can be included in the exchanging error judgement results.

25 It can be considered that, when the base station has the largest received signal power level from a mobile station, a received signal power level of a signal sent from the base station to the mobile station is also largest. Therefore, by sending a response for retransmission control signal from such base station to the mobile station, the possibility of receiving the response by the mobile station can be increased so that retransmission control can be performed with more reliability.

30 The above object is also achieved by a retransmission control apparatus in a base station, including:

35 a part receiving a signal sent from a mobile station;

a part performing error judgment for the signal sent from the mobile station;

a part sending a response which indicates that retransmission is not required to the mobile station when at least one result indicates that there is no error; and

The above object is also achieved by a retransmission control apparatus in a base station, including:

a part performing error judgment for the signal sent from the mobile station;

20           a part sending a first response which  
indicates that retransmission is not required to the  
mobile station when at least one result indicates  
there is no error; and

In the retransmission control apparatus, the first response or the second response is returned to the mobile station by the base station which has the highest received signal power level of up-link packet sent from the mobile station.

According to the above invention, a retransmission control apparatus suitable for performing the retransmission control method can be provided.

BRIEF DESCRIPTION OF THE DRAWINGS

Fig.1A shows a network configuration of a communication system of a first embodiment to which a transmission control method and the apparatus of the present invention are applied;

Fig.1B shows nodes and the corresponding unique IP addresses;

Fig.2A shows a network configuration example of a communication system of a second embodiment to which the retransmission control method and apparatus of the present invention are applied;

Fig.2B shows nodes, the corresponding unique IP addresses and base station multicast addresses;

Fig.3 shows a structure example of a retransmission control table used in the second embodiment;

Fig.4 shows a flowchart of the operation of an base station in the second embodiment.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

In the following, embodiments of the present invention will be described with reference to figures.

Fig.1A shows a network configuration of a communication system of a first embodiment to which the retransmission control method and the apparatus of the present invention are applied.

In the communication system shown in the figure, some base stations receive an up-link signal sent from a mobile station. Each of the base stations performs error judgment for the received signal. In addition, a corresponding base station which is a specific base station with which the mobile station communicates obtains results of error judgment from every base station which received the

5

10

15

20

35



judgment, the result of error judgment can be sent to the base station 2-2 by using the IP address as a destination.

When the base station 2-2 receives the results of error judgment from the base stations 2-1 and 2-3, the base station 2-2 analyzes these results and a result of error judgment in the base station 2-2 itself, and judges whether the results indicate that there is no error in the received up-link signal. When at least one result indicates that there is no error in the received signal, it is not necessary for the mobile station 1 to retransmit the up-link signal because the signal received by a base station which sends the result indicating that there is no error can be used. Therefore, in this case, the base station 2-2 returns ACK to the mobile station 1. When the mobile station 1 receives the ACK, the mobile station 1 does not retransmit the signal.

On the other hand, when the results of error judgment do not include any result indicating that there is no error, that is, when every result indicates that the received up-link signal has an error, any signal which is received by any base station can not be used. Thus, in this case, the base station 2-2 returns NACK to the mobile station 1. When the mobile station 1 receives the NACK, the mobile station 1 retransmits the corresponding up-link signal.

As mentioned above, according to the communication system of this embodiment, not only the base station of the communication partner of the mobile station, but also other base stations which receive an up-link signal from the mobile station judge error of the up-link signal. When there is a base station which judges that there is no error in the received signal, ACK is sent to the mobile

station and the mobile station does not retransmit the corresponding signal. Therefore, since the retransmission processing can be suppressed maximally, efficient transmission control can be realized.

In this embodiment, although the destination to which the result of error judgment is sent is the base station 2-2 with which the mobile station communicates, the destination is not limited to the base station 2-2. The destination can be any other base station.

Next, a second embodiment will be described. Fig.2A shows a network configuration example of a communication system of the second embodiment to which the retransmission control method and apparatus of the present invention are applied.

In the communication system shown in Fig.2A, some base stations receive an up-link signal sent from a mobile station. Each of the base stations performs error judgment of received signal and measures a received signal power level, and the base stations exchange the results of error judgment and the received signal power levels with each other. Then, only when every result of error judgment indicates that there is an error, a base station in which the received signal power level is the largest sends NACK to the mobile station.

This communication system includes a mobile station 1, N base stations 2-1 - 2-N, and a backbone network 3 like the communication system shown in Fig.1A. This communication system forms an IP network in which each of the base stations 2-1 - 2-N has a unique IP address. In addition to the unique IP address, each of the base stations 2-1 - 2-N has a same IP address (base station multicast address) in order to allow multicast communication

as shown in Fig.2B.

This embodiment corresponds to a case where the mobile station 1 sends an up-link signal without specifying a base station of a communication partner of the mobile station. The up-link signal is received by the base stations 2-1 - 2-3.

Each of the base stations 2-1 - 2-3 which received the up-link signal judges whether the received up-link signal includes an error and measures the power level (received power level). The result of error judgment and the received power level is included in a multicast packet which has the base station multicast address as its destination. The multicast packet is sent to other base stations via backbone network 3.

When the base stations 2-1 - 2-3 receive the multicast packet, each base station generates a retransmission control table from the results of error judgment and the received signal power levels included in the multicast packets and the result of error judgment and the received signal power level obtained by the base station itself.

Fig.3 shows a structure example of the retransmission control table. The retransmission control table includes mobile station addresses, base station addresses, results of error judgment and received signal power levels. The mobile station addresses are IP addresses of mobile stations which sent the up-link signal, and the base station addresses are IP addresses of base stations which received the up-link signal. The mobile station address, the base station address, the result of error judgment and the received signal power level are associated with each other.

After generating the retransmission control table, each of the base stations 2-1 - 2-3 judges whether the received signal power level of

the base station itself is larger than any other received signal power levels in the retransmission control table. The base station having the largest received signal power level analyzes the results of error judgment in the retransmission table and judges whether the table includes an result of error judgment indicating that the received up-link signal includes no error.

In the same way as the first embodiment, when the table includes the result of error judgment indicating the received up-link signal includes no error, the base station sends ACK to the mobile station. The mobile station which receives ACK does not retransmit the signal. On the other hand, when the table does not include the result of error judgment indicating no error, that is, when every result of error judgment indicates that the received up-link signal includes an error, the base station sends NACK to the mobile station. The mobile station which receives NACK retransmits the signal.

Fig.4 shows a flowchart of the operation of the base station in the second embodiment. When the base stations 2-1 - 2-3 receive the up-link signal from the mobile station 1 in step 1, each base station judges whether the up-link signal includes an error and measures the received signal power level in step 2. Then, each base station sends the multicast packet which includes the result of error judgment and the received signal power level, and receives multicast packets from other base stations in step 3.

Next, each base station generates the retransmission control table from the results of error judgment and the received signal power levels included in the multicast packets, and the result of error judgment and the received signal power level of the base station itself in step 4. Then, each

5

10

20

25

35

power level for the up-link signal sends ACK or NACK to the mobile station. Therefore, since it can be considered that a received signal power level in the mobile station is large if the base station having the largest received signal power level sends a signal to the mobile station, the possibility of receiving ACK or NACK by the mobile station can be increased. As a result, retransmission control can be performed with more reliability.

As mentioned above, according to the present invention, each of base stations which receive a signal from a mobile station performs error judgment of the signal. When there is at least one base station which judges that the signal includes no error, ACK which indicates that retransmission is unnecessary is sent to the mobile station so that retransmission is not performed. Therefore, retransmission process can be suppressed maximally, efficient retransmission control can be possible, load of performing retransmission process can be decreased, and communication channels can be used effectively.

The present invention is not limited to the specifically disclosed embodiments, and variations and modifications may be made without departing from the scope of the invention.

30

35